

Bring **life** to your communications

Versatile, affordable indoor electronic messaging.



The VCI 300 Series is one of the most versatile single-line indoor electronic message displays available today. With the 300 series you can provide constant employee communication, post real-time information, boost morale, or advertise company-wide events — all from your desktop PC or easy-to-use handheld keyboard.

These versatile displays keep you connected with employees throughout the day and company wide. These visually superior, easy-to-program signs will help you create a new vision for your business communications.

Features

- Character size 3.1"
- Stores & displays over 80 messages
- 2 length options available
- Keyboard programmable from 30 ft.
- 8 brilliant colors & 3 rainbow effects
- 5 Operating speeds
- 6 Character fonts
- One year USA Factory Warranty, Indoor use only



ElectronicSigns.com

800-341-6397

www.electronic signs.com

VCI 300 Series Specifications

Sizes	320C	330C
Case Dimensions: (With power supply)	57.4"L x 3.8"D x 5.5"H (145.8 cmL x 9.7 cmD x 14.0 cmH)	84.4"L x 3.8"D x 5.5"H (214.3 cmL x 9.7 cmD x 14.0 cmH)
Approximate Weight:	12.5 lbs. (5.7 kg.)	17 lbs. (7.7 kg.)
Display Dimensions:	54"L x 3.1"H (137.2 cmL x 7.9 cmH)	81"L x 3.1"H (205.7 cmL x 7.9 cmH)
Display Array	120 x 7 pixels	180 x 7 pixels
Characters Displayed	20 minimum/typical 34 condensed rotate mode	30 minimum/typical 51 condensed rotate mode
Display Memory	29,500	28,500

Pixel Size (Diameter):	.276" (.7 cm)
Pixel (LED) Color:	Eight colors and three rainbow effects (tricolor in the condensed rotate mode)
Center-to-Center Pixel Spacing (Pitch):	.45" (1.1 cm)
Character Size	3.1" (7.6 cm)
Character Set:	International Character Set, Block (sans serif), decorative (serif), upper/lower case, slim, wide
Memory Retention:	One month typical
Message Capacity:	81 different messages can be stored and displayed
Message Operating Modes:	<ul style="list-style-type: none"> – 25 consisting of: Automode™, Hold, Roll (6 directions), Rotate, Sparkle-On, Twinkle, Interlock, Wipe (six directions), Spray-On, Slide Across, Starburst, Switch, Flash, Snow, Scroll and condensed rotate – Continuous message entry with automatic centering in any mode – User programmable logos and graphics – Five variable speed controls
Built-In Animations:	Cherry Bomb Exploding, Don't Drink and Drive, Fireworks, Slot Machine, No Smoking, Running Animal, Moving Auto, Welcome (in script), Thank You (in script)
Real-Time Clock:	Date and time, 12 or 24 hour format, maintains accurate time without power for up to 30 days typical

Serial Computer Interface:	RS232 and RS485 (multi-drop networking for up to 255 displays) <i>Options</i> Wireless Interface –Ethernet LAN interface
Power:	100 VAC to 240 VAC and 50/60 Hz for all models: 40 watts (320C) and 50 watts (330C)
Power Cord Length:	US: 10' maximum Europe, Australia, UK: 3.3m maximum
Keyboard:	Handheld, Eurostyle, IR remote
Case Material:	Extruded aluminum
Limited Warranty:	One-year parts and labor, factory servicing
Agency Approvals:	<ul style="list-style-type: none"> – Listed to ANSI/UL 1950-Second Edition (US) and CAN/CSA-22.2 No.950-M89 (Canada) – Complies with EN 60950: 1992 (Europe) and AS/NZS 3260-1993 (Australia/New Zealand) – FCC Part 15 Class A – Marked
Operating Temperature:	32° to 120°F, 0° to 49°C
Humidity Range:	0% to 95% non-condensing
Mounting:	Hardware to accommodate ceiling or wall mounting